

Specifications ABI Aluflex Medium Combination



SPECIFICATIES	
Height aluminum	13 mm
Width aluminum	30 mm
Thickness aluminum	1,15 mm
Profile distance	4 mm
Connection profiles	PVC connection strip
Bottom profiles	Equipped with sound-damping and anti-slip layer
Standard colour aluminum	Brute
Optional	Anodizing in 24 colours
Maximum load	2.100 kg per 100 cm ²
Classification of burning behaviour	B _{fl} -s1
Classification of slip-resistance	R10-R13
Total weight of mat	approx. 14 kg / m ²
Total height of mat	<u>Inlays:</u> Brushes: 20 mm Needle punch: 18 mm Rubber: 18 mm Carpet: 17 mm

OPTIONS INLAYS		
Brushes	100% nylon 6.6 colour-solid	Colours: B01 Black B09 Mint green B02 Dark grey B10 Blue B03 Light grey B11 Dark red B04 Brown B12 Red B05 Yellow B13 Orange B06 Tan B14 Purple B07 Dark Green B15 White B08 Green B16 Light blue
Rubber	EPDM rubber with ribbed structure	Colour: black
Needle punch	100% polypropylene	Standard colours: black, grey en cocos <i>Other colours are also possible</i>
Carpet	100% polyamide	Standard colours: 007 anthracite 014 grey 016 grigio 052 graphite 070 sand 071 taupe uni <i>Other colours are also possible</i>