

# Specifications ABI Duplomat 18mm Buffed Rubber



| SPECIFICATIONS                      |  |
|-------------------------------------|--|
| Height aluminum                     | 16 mm  |
| Width aluminum                      | 16 mm  |
| Thickness aluminum                  | 1,5 mm   |
| Inlay material                      | Vulcanized layered rubber strips with pre-coloured fabrics (colourfast). |
| Height inlay material               | 18 mm  |
| Width inlay material                | 15 mm  |
| Connection profiles                 | Galvanized steel wire pins of thickness 2.5 mm                           |
| Standard aluminum                   | Brute  |
| Optional aluminum                   | Anodizing in 24 colours  |
| Optional inlays                     | Single version<br>Double version<br>Triple version                       |
| Maximum weight                      | 2.900 kg per 100 cm <sup>2</sup>   |
| Classification of burning behaviour | C <sub>n</sub> -s1   |
| Classification of slip-resistance   | R11  |
| Total weight of mat                 | approx. 17 kg / m <sup>2</sup>   |
| Total height of mat                 | 18 mm  |

| OPTIONS INLAYS    |                                 |
|-------------------|---------------------------------|
| Buffed Rubber     | Colours: Grey<br>Black<br>Zebra |
| Open construction | With open EPDM-spacers          |